

DC-2510

ULTRA CLEAR RIGID EPOXY DOMING RESIN

DESCRIPTION:

Deco-Coat 2510 Resin System is a two component, low viscosity, rigid epoxy decorative coating. This high gloss resin is “water clear.” It is formulated with UV stabilizers and other proprietary additives which helps prevent premature yellowing & degradation.

While providing optimum clarity the DC-2510 enhances the substrates & images to which it is applied. It will cure at room temperature or may be accelerated with mild heat and contains a proprietary air release additive which allows for an air bubble free high gloss dome coating.

ULTRA CLEAR RIGID EPOXY DOMING APPLICATIONS:

- Labels
- Plaques
- Emblems
- Badges
- Lapel Pins
- Key Tags
- Luggage Tags
- Ornaments

INSTRUCTIONS FOR USE:

1. By weight mix 2 parts DC-2510 Epoxy Resin to 1 part DC-890C.
2. Mix thoroughly and uniformly. Be careful not to whip air into mixture.
3. Dispense mixed epoxy pneumatically or with squeeze bottles.
4. Let cure at room temperature overnight or accelerate with mild heat, 80-100°F for 2-4 hours.

AVAILABILITY:

DC-2510 and DC-890 C are available in quarts, gallons, and five-gallon pails.

IMPORTANT:

EPOXIES, ETC. MAKES NO EXPRESS OR IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS OR OTHERWISE WITH RESPECT TO ITS PRODUCTS. The information in this brochure is based on data obtained by our own research and is considered reliable. However, no warranty is expressed or implied regarding the accuracy of these data, the results to be obtained from the use thereof, or that any such use will not infringe any patent. The properties given are typical values and are not intended for use in preparing specifications. This information is furnished upon the condition that the person receiving it shall make his own tests to determine the suitability thereof for his particular purpose.

06/14